RevNo	Revision note	Date	Signature	Checked



PIN OUT



NOTES:

1:100% short,open and miss wire test.

2:Insulation resistance:DC300V 10MΩ(Min)

Conduction resistance 5Ω(Max)

NO.	MATERIAL	DESCRIPTION	QTY.	UNIT
⑥	SCREW	#4-40UNC SCREW,NICKEL PLATED,BLACK PVC	2	PCS
⑤	OUTER MOLDED	WHITE 45P PVC	0.078	KG
④	INNER MOLDED	LDPE	0.024	KG
③	CONNECTOR	DISPLAYPORT MALE WITH PCB BOARD,THE PIN GOLD PLATED,THE SHELL FOR GOLD PLATING	1	PCS
②	CONNECTOR	DVI 24+1 MALE,THE PIN GOLD PLATED,THE SHELL FOR GOLD PLATING	1	PCS
①	CABLE	(1P*30#+D+AL+MYLAR)*4C+1P*30#+3C*30#+F+ADB JACKET:BLACK PVC,OD:7.3±0.2MM	5000	MM

Itemref	Quantity	Title/Name,designation,material,dimension etc		Article No./Reference	
Designed by		Checked by	Approved by - date OCT 23.2014	File name DVI 24+1 TO DP 5M	Date OCT 23.2014	Scale FREE
ANGLE:		DVI 24+1/M-DP/M,BLACK, 5M			
UNIT:MM		24 0212		Edition 1	Sheet 1/1